



**ICEUS, Inc.**  
**Utility Division**

**Presents**

# **Gel-Away LVP Solvent/Degreaser Cable And Tool Cleaner**

**With A VOC Content Of Less Than 25 Grams Per Liter**

**Gel-Away LVP was engineered to safely remove water blocking compounds and cable gels from filled (pic) copper cable, cladding and tubes in fiber optic cable and filled CATV cable. It is water rinseable and safe to use on tools and equipment.**

- **Gel-Away LVP will also remove C-cement, tar, difficult grease, oils, uncured or partially cured resins, waxes, and gums. It will not harm most painted surfaces, metals, or plastics.**
- **The Gel-Away LVP formula has been in use in industry since 2003. It has passed compatibility testing with cable insulation and components, and plastics and metals.**
- **Gel-Away LVP can be used as a safe replacement for chlorinated solvents, kerosene, mineral spirits and**

**other hazardous solvents. It offers excellent cleaning effectiveness without any of the health, environmental, and disposal problems associated with other hazardous products. Gel-Away LVP can be rinsed off with water for easy jobsite cleanup.**

- **When used as directed, Gel-Away LVP has been found to have no deleterious effects on cables, splice materials, or tools. It does not contain any halogenated solvents or suspected carcinogens, teratogens, or mutagens. Gel-Away LVP, in its pure unused form, is not listed or defined as a hazardous waste; therefore, for most applications, it does not require the use of expensive hazardous chemical waste handling and disposal methods. With a Tag Closed Cup flash point of >185°F (per ASTM D56-90), Gel-Away LVP is OSHA classified as a class III combustible liquid.**

- Ideal For Use In Cold Environments
- Field Proven Formula Since 2003
- Tested For Complete Compatibility With Plastics & Materials
- Rinses Off With Water At Jobsite
- Contains No CFC's Or HCFC's
- No Ozone Depleting Potential
- Classified As A Low Vapor Pressure Exempt VOC in California & Other States
- No SARA 312, 313 Reportables
- Environmentally Responsible
- Worker Friendly
- OSHA Classified As Combustible Class III; Not Rated As Flammable
- Not Regulated By DOT In Containers Of 119 Gallons Or Less

ITEM#	DESCRIPTION	PACKAGING	SHIPPING WEIGHT
GA-LVP-55	55 gallon plastic drum	1 drum	385 LBS
GA-LVP-01	1 gallon plastic jug	6 jugs	44 LBS
GA-LVP-PW-250	7.5" x 14" saturated wipes in a pop up bucket	1 bucket (250 wipes)	11 LBS

Distributed/Represented By:

**ICEUS, Inc.**

**Chemical & Topical Products**



305-B Scarlet Blvd., Oldsmar, FL 34677 Ph: 813-854-2777 Fax: 813-854-2662

website: [www.iceus.com](http://www.iceus.com)