



ICEUS, Inc. Industrial Division

Presents

The TECHSOLV Line!

A Range of Engineered Solvent Products Designed for
Industrial Applications

TECHSOLV-EF-LVP DEGREASER

TECHSOLV-EF-LVP (Low Vapor Pressure) is a degreasing solvent engineered to be a full strength cleaner which performs well in most industrial applications. It has a VOC content of less than 25 grams per liter.

TECHSOLV-EF-LVP will evaporate in 5 to 10 minutes when wiped or blown to a thin film. In open containers, its evaporation rate is slightly slower than water. This means that less solvent is used in normal degreasing operations which leads to significant dollar savings annually.

TECHSOLV-EF-LVP has a low surface tension 25 dynes per centimeter at 25°C, which enables it to reach extremely small surface blemishes and remove minute contaminants.

TECHSOLV-EF-LVP has a Tag Closed Cup flash point of >185°F [per ASTM-D56], giving it an OSHA classification of combustible class III. In containers of less than 119 gallons, it is not regulated by the DOT. It is classified as not hazardous by SARA Title III, Sections 311, 312, or 313. It is listed under TSCA.

TECHSOLV-EF-LVP has been evaluated and determined to meet the Low Vapor Pressure [LVP] exemption set by the California Air Resources Board [CARB] for volatile organic compounds in consumer products [California Code of Regulations, Title 17, Article 2, Section 94510]. Its vapor pressure mmHg is less than 0.1 at 68°F.

TECHSOLV-EF-LVP has a recommended Occupational Exposure Limit [OEL], TWA, of 300 ppm. It has a very slight citrus odor. It contains no CFCs or HCFCs.

TECHSOLV-EF-LVP is non-corrosive to metals such as copper, aluminum, brass, magnesium, and steel. The product conforms to the requirements of ASTM F945 [stress crack corrosion of titanium alloys] and ARP 1755A [stock loss corrosion] tests.

TECHSOLV-EF-LVP is a non conductive fluid with a very high Basic Insulation Level [BIL]. Its dielectric strength is >29 KV.

TECHSOLV-EF-LVP is available in packaging that meets most industrial situations. It may be purchased in 55 Gallon Non-Conductive, Recyclable Plastic Drums, 5 Gallon Plastic Pails, 32 Ounce Plastic Squirt Top Bottles, and Prep Wipes Containers. Specialty packaging is available if volume warrants.

ITEM#	DESCRIPTION	PACKAGING	SHIPPING WEIGHT
TS-EF-LVP-55	55 gallon plastic drum	1 drum	385 LBS
TS-EF-LVP-05	5 gallon plastic pail	1 pail	36 LBS
TS-EF-LVP-32	32 ounce bottles w/squirt tops	12 bottles	22 LBS
TS-EF-LVP-PW-250	7.5" x 14" saturated wipes in a pop up buckets	1 bucket	11 LBS

Distributed/Represented By:

ICEUS, Inc.

Chemical & Topical Products



305-B Scarlet Blvd., Oldsmar, FL 34677 Ph: 813-854-2777 Fax: 813-854-2662

www.iceus.com